

REVISION DATE:2000-12-18

SAFETY DATA SHEET

CARBOLINE E19 PRIMER / CARBOGUARD E19, PART B

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND THE COMPANY:

PRODUCT NAME: CARBOLINE E19 PRIMER / CARBOGUARD E19, PART B
PART No.: 8101-0-900
IN-HOUSE No.: 8101-0-900
SUPPLIER: STAR MALING OG LAKKFABRIKK A/S/ CARBOLINE NORGE A/S
Postboks 593
3412 LIERSTRANDA
NORWAY
Tel: 32-857300
Fax: 32-857495
MANUFACTURER: STAR MALING OG LAKKFABRIKK A/S
Postboks 593
3412 LIERSTRANDA
Tel: 32-857300
Fax: 32-857495

2. COMPOSITION/INFORMATION ON INGREDIENTS:

NAME	CAS No.:	CONTENT	SYMBOL:	RISK:
2-METHYLPROPAN-1-OL	78-83-1	5-10 %	Xn	R-20
DIMER REACTION FROM FATTY ACID AND POLYAMINE		30-60 %	Xi	R-41
XYLENE, MIXTURE	1330-20-7	30-60 %	Xn	R-38, 20/21

COMPOSITION COMMENTS: Key to the symbols: Tx= Very toxic, T= Toxic, C= Corrosive, Xn= Harmful, Xi= Irritant, IK= Not classified, E= Explosive, O= Oxidizing, Fx= Extremely flammable, F=Highly flammable, N= Dangerous to the environment, M= Mutagenic, A= Sensitizing, K= Carcinogenic, R= Toxic to reproduction

3. HAZARDS IDENTIFICATION:

Flammable. Harmful by inhalation and in contact with skin.
Irritating to eyes and skin. No available environmental data on

this product, ref.section 12.

4. FIRST AID MEASURES:

GENERAL:	In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person.
INHALATION:	Move the exposed person to fresh air at once. Perform artificial respiration if breathing has stopped. When risk of unconsciousness, place and transport the victim in secured sideposition. Keep the affected person warm and at rest. Get prompt medical attention.
INGESTION:	Do not induce vomiting. If vomiting occurs, the head should be kept low so that stomach vomit doesn't enter the lungs. Provide rest, warmth and fresh air. Get medical attention.
SKIN:	Remove affected person from source of contamination. Promptly wash contaminated skin with soap or mild detergent and water. Promptly remove clothing if soaked through and wash as above. Do NOT use solvents or thinners.
EYES:	Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes and get medical attention. Make sure to remove any contact lenses from the eyes before rinsing.

5. FIRE FIGHTING MEASURES:

EXTINGUISHING MEDIA:	Dry chemicals, sand, dolomite etc. Powder, foam or CO2.
SPECIAL FIRE FIGHTING PROCEDURES:	Avoid water in straight hose stream; will scatter and spread fire. Move container from fire area if it can be done without risk.
UNUSUAL FIRE & EXPLOSION HAZARDS:	Generates massive smoke during fire. Solvent vapours may form explosive mixtures with air. Vapours are heavier than air and may spread near ground to sources of ignition.
PROTECTIVE MEASURES IN FIRE:	Appropriate breathing apparatus may be required.

6. ACCIDENTAL RELEASE MEASURES:

PERSONAL PRECAUTION IN SPILL:	Wear necessary protective equipment, ref.section 8.
SPILL CLEANUP METHODS:	Provide ventilation and confine spill. Do not allow runoff to sewer. Collect with absorbent, non-combustible material into suitable containers.

7. HANDLING AND STORAGE:

USAGE PRECAUTIONS: Keep away from heat, sparks and open flame. Avoid spilling, skin and eye contact. Ventilate well, avoid breathing vapours. Use approved respirator if air contamination is above accepted level. Read and follow manufacturer's recommendations. Wear necessary protective equipment, ref. section 8.

STORAGE PRECAUTIONS: Keep in cool, dry, ventilated storage and closed containers.

STORAGE CRITERIA: Flammable liquid storage.

8. EXPOSURE CONTROLS AND PERSONAL PROTECTION:

INGREDIENT NAME:	CAS No.:	STD	ST EXP 15 Min	LT EXP 8 Hrs
XYLENE, MIXTURE	1330-20-7	OES.	435 mg/m ³ (Sk)	650 mg/m ³ (Sk)
2-METHYLPROPAN-1-OL	78-83-1	OES.	105 mg/m ³	225 mg/m ³

INGREDIENT COMMENTS: OES = Occupational Exposure Standard.

PROTECTIVE EQUIPMENT:



PROCESS CONDITIONS:

VENTILATION: All handling to take place in well ventilated area.

RESPIRATORS: At work in confined or poorly ventilated spaces, respiratory protection with air supply must be used. Wear respiratory protection with combination filter (dust and gas filter) during spraying operations. Gas cartridge (organic substances).

PROTECTIVE GLOVES: Use protective gloves made of: Viton rubber (fluor rubber). Polyvinyl alcohol (PVA).

EYE PROTECTION: If risk of splashing, wear safety goggles or face shield.

OTHER PROTECTION: Provide eyewash, quick drench.

HYGIENIC WORK PRACTICES: Wash at the end of each work shift and before eating, smoking and using the toilet. Wash promptly if skin becomes wet or contaminated. Promptly remove any clothing that becomes wet. Use appropriate hand lotion to prevent defatting and cracking of skin.

9. PHYSICAL AND CHEMICAL PROPERTIES:

APPEARANCE: Fluid.

COLOUR: Colourless.

ODOUR/TASTE: Solvent.

DENSITY/SPECIFIC GRAVITY (g/ml): 0.94

VAPOUR DENSITY (air=1): > 1
FLASH POINT (°C): 25
AUTO IGNITION TEMP. (°C): 340
FLAMMABILITY LIMIT - LOWER 1
(%):
FLAMMABILITY LIMIT - UPPER 11.30
(%):

10. STABILITY AND REACTIVITY:

STABILITY: Avoid: Heat, sparks, flames.
HAZARDOUS DECOMP. PRODUCTS: Toxic gases/vapours/fumes of: Carbon monoxide (CO). Carbon dioxide (CO₂). Nitrous gases (NO_x). black smoke

11. TOXICOLOGICAL INFORMATION:

HEALTH WARNINGS: Solvent vapours are hazardous and may cause nausea, sickness and headaches. Contact with this chemical may cause: Skin drying with risk of formation of eczema. Vapour may irritate respiratory system or lungs. Prolonged or repeated contact: Brain damage.
MEDICAL CONSIDERATIONS: Chronic solvent-induced symptoms may give untypical (neurasthenically produced) impression of disease.

12. ECOLOGICAL INFORMATION:

ECOLOGICAL INFORMATION: No available environmental data on this product.
Environmental data, Xylen (Cas.nr. 1330-20-7) :Do not bioaccumulate in aquatic environment. LC50 96h (fish): 2-11 mg/l Roccus saxatilis, 8,2 mg/l Salmo gairdneri, 13,5 mg/l Lepomis macrarchirus, 21,0 mg/l Pimephales promelas. EC50 24h (Daphnia): 1-5 mg/l, IC50 72h (algae): 3-5 mg/l Selenastrum sp. Degradation: OECD-test 301C: Readily degradable, BOD5/COD: ca.0,6. Bioaccumulation: BCF:80 fisk (calculated) 21-24 Anguilla japonica, Log Pow: 3,11 - 3,20. Environmental data, isobutanol (Cas.no.78-83-1) , readily degradable BOD5/COD:0,8, Bioaccumulation Log Pow >3, LC50 Guldid, 48h: 1200 mg/l, BC50 Daphnia magna, 24h: 1880 mg/l.

13. DISPOSAL CONSIDERATIONS:

DISPOSAL METHODS: Wastes should be delivered as hazardous waste. Do not allow runoff to sewer, waterway or ground.

WASTE CLASS: . 08 01 02.

14. TRANSPORT INFORMATION:

UN No. ROAD: 1263
ADR CLASS: Class 3: Flammable liquids.
ADR ITEM No.: 31c
RID CLASS No.: 3
RID ITEM No.: 31c
IMDG CLASS: 3.3
IMDG PAGE No.: 3372
EmS No.: 3-05
MFAG TABLE No.: 310
AIR PACK GR.: III

15. REGULATORY INFORMATION:

LABEL FOR SUPPLY:



RISK PHRASES: R-10 Flammable.
R-20/21 Harmful by inhalation and in contact with skin.
R-36/38 Irritating to eyes and skin.

SAFETY PHRASES: S-23,13 Do not breathe fumes/vapour/aerosol mist.
S-25 Avoid contact with eyes.
S-38 In case of insufficient ventilation, wear suitable respiratory equipment.
S-42 During fumigation/spraying wear suitable respiratory equipment.
S-51 Use only in well ventilated areas.

16. OTHER INFORMATION:

USER NOTES:

The information in this safety-data sheet is based on our current knowledge. The user's working conditions are beyond our supervision. The responsibility to fulfill the demands determined in the national regulations always lies with the user. The information should be understood as a description of those safety requirements which are demanded on the product and is no guarantee for the properties of the product. This information may only be quoted with the producer's permit. The safety data sheet in Norwegian is OLF APPROVED.

ISSUED BY:

STAR MALING OG LAKKFABRIKK A/S

REVISION DATE:

2000-12-18

REV. No./REPL. SDS

2000-06-21

GENERATED:**DATE:**

2000-12-18

SIGNATURE:

I.V