

TRS Non Skid Powder ————— **0994**

Product description: TRS Non Skid Powder is flame dried silica sand of which the average particle size is approximately 0/5 - 1 millimeter.

Recommended use: To obtain anti-skid properties on decks and other areas where a skid –proof surface is required.

Physical Constants:

Colour	: white
Specific gravity	: 1/45 (approx..) kg/liter
Particle Shape	: Grit

Remarks: TRS Non Skid Powder should be sprinkled evenly on the surface immediately upon application of the penultimate coat of the paint system while the paint is still wet. Consumption approximately 2.5 kg/5.5 lbs of Rangafarin to 25 so..m/ 270 sq. feet. When the paint is dry, sweep up surplus grit and apply the final coat. Rangafarin's TRS Non Skid Powder should be kept dry and clean. Do not mix contaminated sweepings with new supplies.

Safety: Handle with care. Before and during use, observe all safety labels on packaging and paint containers, Consult Rangafarin Material safety data sheets and follow all local or national safety regulation. This goes for personal protection such as, but not limited to, protection of lungs, eyes and of the skin, medical treatment in case of swallowing the paint or in case of other direct contact with the paint. Take necessary precautions against possible risks of fire or explosions as well as protection of the environment. Apply only in well ventilated areas and ensure that adequate forced ventilation exists when applying paint in confined spaces or when the air is stagnant